

Method and device for access communication/control

The present invention relates to a method and a device for access communication/control.

**5 Background of the invention**

Code locks, card readers, or such-to corresponding functions of a visiting preauthorized mobile telephone as disclosed in e.g. WO 00/62521, biometrical readers etc. all have a common disadvantage; in a varying degree they form a bar for occasional and welcome visitors/users (hereinafter "visitors"). This disadvantage is particularly obvious when visiting  
10 a tenant or similar in a locked building. Furthermore, the possibility for the visited party to make a "final" judgement/authentication based on from case to case varying situation may not exist. In order to overcome this disadvantage, in particular with regard to tenant buildings, so called entrance telephones, often combined with code locks, have been introduced, which basically can be divided into two groups: A - intercom systems, among  
15 which among which also in the trade so called 'no telephone bill' systems (e.g. US 3,484,561), which by switching, hardwiring etc. connects to the separate incoming telephone lines of a building at the subscriber side of the Central Office switches, can be counted; and B - "entrance telephone systems" (e.g. SE 7308086-3). "Hybrids" therebetween also exist (e.g. US 5,046,083).

20

Group A has normally, particularly in larger installations, high complexity and considerable costs for hardware/installation, but involve no running costs as long as the system operates in intended fashion.

25 Group B has, despite simplicity and low initial costs, another major disadvantage, namely continuous running costs, i.e. a building having such an installation involves, apart from payment of a running basic subscriber fee, also pay for completed calls, which on one hand makes it expensive, and on the other is unfair for tenants having few visitors if the running costs are divided equally and charged on top of the rent paid by the tenants.

30

Various solutions aimed to minimize these problems have been proposed in e.g. SE 9901299-9 and WO 99/44353, each having features that might be of interest for more advanced installations/applications, but less suited for a conventional tenant building and other more common applications.

35

### Object of the invention

One object of the present invention is to disclose a simple, low cost and easily installed entrance telephone solution, which does not involve high running costs, but offers good security, full speech/data communication between a calling visitor and a called tenant or  
 5 similar (or for example an automatic answering machine), hereinafter stated as "B-replier"; and exclusive possibility for the called party to reply to the call, and thereafter, by own choice, perform the control function (e.g. open the entrance lock), i.e. all substantial and characteristic features of entrance telephones etc., and which advantageously can be combined with a special code lock, but also card/biometrical reader etc. (and TV camera,  
 10 one or more direct intercom line, display, keypad, IR/RF-reader/transponder, speech(audio)parts and so on). Moreover, instead of a tenant for door opening, a visitor before e.g. a machine for performing some requested service can in another preferred embodiment of the present invention, be offered possibility to likewise contact a service provider, man or machine, acting as B-replier, which in its turn likewise can influence the  
 15 visited machine and so perform an authorized service function, i.e. provide access, where access can include opening as well as access to services and goods.

Another object of the invention is to facilitate two-way communication between a service provider, man or machine, and a machine performing requested services, whereby a  
 20 user's mobile telephone is used for establishing communication with a service provider, and as a following step, while the call is maintained, the mobile telephone is placed into a "cradle" having a microphone and a loudspeaker connected to a service providing machine, or other contrivance for short range communication with a mobile phone, e.g. IR, Bluetooth, and which so is passed on by the mobile (hereinafter commonly referred to as  
 25 "cradle"), thereby establishing a two-way signal or data transfer link between the service provider and the service providing machine. On completion of accepted transmission, the service providing machine is actuated to perform requested service. While one preferred embodiment hereof for the rest maintains a to be herein disclosed conventional telephone network connection/usage, and the thus established data link primarily is used to enhance  
 30 and speed up a transaction, this also makes another to be herein disclosed preferred embodiment feasible, where no own permanent connection to a signal transferring network is required for the service providing machine but by means of mentioned (and consenting) mobile telephone's regular subscription a virtual telephone network connection is instead established.

### **Description of preferred embodiments**

Since the present invention should be able to handle numerical codes, such as telephone numbers, it will be described with reference to a preferred embodiment which is integrated with a conventional code lock, i.e. with a visitor accessible key pad which in a conventional way will be seen by a visitor approaching the entrance (apart from perhaps instructions, a board with names of tenants etc. for this particular type of (entrance) application); and since also card and biometrical readers as output deliver numerical codes, they are easily connected, and not described further hereafter. A lock is normally connected for entrance applications; for other applications other control means as required.

10

In difference to the disclosure made in SE 9901299-9. the present invention does not require any response to any type of direct signalling from an (adjacent) mobile telephone. No control is thus made e.g. of number input performed by a visitor. However, it offers by its signal response capacity a visitor the possibility (which always exists, but without this capacity) to call by his own (mobile) telephone an authorized replying party, the B-replier, whereafter same handles validation, active control signalling etc.. A device according to the present invention has namely in one preferred embodiment its own permanent connection (subscription or the like and thereby allocated telephone number/address, hereinafter commonly referred to as "telephone number") to a regular, operator administered telecommunication's network (hereinafter commonly referred to as "telephone network"), fixed or mobile, also e.g. Internet (IP); (W)LAN; MiniCall (pager) etc., which in a conventional way offers the service "number ID" (Caller-ID). A device according to the present invention should further accept calls and the "ID" information and decode and treat same. However, it is not necessary, for the actual functionality, that the device according to the invention uses its telephone network connection for outgoing calls (as with regard to the aforementioned Group B); typically can the device according to the invention not dial telephone numbers - only reply to incoming calls - which does not rule out that the network connection can be used by e.g. caretakers, alarm diallers, etc. to access the telephone network, but then typically not in connection with the entrance telephone, other than when a combination system is implemented. A combination with alarms (preferably having priority) is advantageous, since the degree of use for the telephone network connection is increased and responsive control signals etc. can be sent back to alarm site.

35 This embodiment offers thus the visitor (or rather the tenants) direct code lock services,

but on top of that complete entrance telephone services with use of the visitor's own (mobile) telephone, on which the visitor initially dials the telephone number of the tenant or similar. This can be made at a distance (in which case also by a fixed network connected telephone) or (most often) by the "entrance" (in which case depression of a key  
 5 on the device according to the invention - even though not necessary - may start up the procedure and thus confirm proximity of the visitor). Should the number dialled be a number allocated to the device according to the invention, the device may via the number ID check the authority of the "visitor" for any possible direct function/signal response obtainable via the device according to the invention, which may, particularly over a  
 10 distance, be a desirable feature for the invention, perhaps in particular for applications involving apparatus/programming etc..

Should the number dialled relate to the telephone of a tenant or other service/access provider (fixed or mobile, and which should not have the service "protected number"  
 15 activated in order to operate according to the invention), this party, the B-replier, can answer and per conversation etc. establish that it is an "entrance call". If a lock opening function or other function by the device according to the invention is desired, the B-replier now activates a 3-party conference call (or ends the entrance call; after possibly having instructed the visitor how to proceed; if audiopart, same can then "take over" the  
 20 conversation; a visitor can also have used other means than a telephone - or other telecommunication's instrument like e.g. "IP-phone"; PC etc., hereinafter commonly referred to as "telephone" - call to a B-replier's corresponding telecom instrument, e.g. SMS; ring, a possibly cordless, bell; shouting; fixed time appointment, for indicating presence and wish for access) and dials the number to the device according to the  
 25 invention (or a visitor can call a (mobile; mobile to mobile often cheaper or in some subscription etc. formats even free to a chosen party's number) telephone of a B-replier, and same can, maintaining conversation and thus supervising of entry, dial the number on another (due to very high immunity against so called caller-ID spoofing that increasingly has emerged on IP- and mobilephony and against which countermeasures are trying to  
 30 find, and also cost factors, preferably traditionally fixed - "landline" - connected; and fixed to fixed often cheaper - if the device, as is herein on much the same grounds generally preferred, also is landline connected) telephone, where this number also possibly can be preprogrammed as a short number). Via its number ID a check is performed on the telephone number of the B-replier against a list of programmed numbers in order establish  
 35 the authority of the B-replier and what response same is authorized, e.g. time zone, control

means, action etc.. When the authority has been established (for example, a “tenant of the building”), the device will listen for control signals (and also send back its own control/status data etc.) via existing connection (for example DTM for entrance telephone systems; and more advanced duplex modem data signalling for apparatus applications),  
 5 and act accordingly. Since the visitor in this situation is disconnected, the above signalling takes place exclusively between authorized B-replier and the device according to the invention. When the device according to the invention has accomplished required action, and possibly also confirmed this, the call is disconnected.

- 10 When looking at the costs, the result is: Simple technology and installation results in low costs. Connection (subscription) is the only common cost for the building and may also be favourably negotiated with one of the many today existing operators (since additional income due to call fees for calls via its network might be involved, particularly in connection with any 020 applications = free or sponsored call number). In e.g. houses with more than  
 15 one entrance door, one central unit having the sole telephone network connection, can “serve” multiple doors; incoming number also carrying ID for which door.

The visitor pays for his call via his telephone bill, unless the invention (probably most often in apparatus/machine applications, or small offices etc. among tenants of an apartment  
 20 building) offers 020-numbers to preprogrammed B-replier(s), credited when transaction is performed.

The B-replier accepts the cost for its own calls to the device according to the invention, and in difference to the aforementioned Group B there is no cost for a refused opening  
 25 operation, since no call to the device according to the invention is necessary.

Should a tenant be preprogrammed as a B-replier via a mobile telephone (telephones connected to a fixed network are not relevant) and brings same when leaving the building, entrance lock opening can be performed without regard to geographical position and also  
 30 when no visitor has made a call, i.e. such a mobile telephone can open the entrance lock for the tenant if a call is made to the device according to the invention and if subsequently an opening command is made. On the other hand, this could involve a call charge (opening code via a keypad is free of charge), but it offers an alternative when no keypad exists or same is disconnected (time zone operated).

In addition to the above described embodiment of a preferred embodiment can be mentioned: Even though a keypad etc. accessible to visitors is not required for the entrance call function - a basic installation would actually only need to state its presence by means of an instruction, pushbutton etc., as previously described, addition of a keypad  
 5 has many advantages, apart from the practical operation of a code lock in general. Thus a keypad can be used for so called alarm shunt; in situ programming (where there is no modem, or using PC/laptop therefore, which otherwise is preferable, for some reason not is done); control/opening possibility for not "entryphone-programmed" tenants etc..

- 10 When used for apparatus applications, e.g. automatic machines, a keypad can also be used for extended communication between visitor and B-replier in a device according to the invention, for example card PIN-codes etc.

The opening function command can be further protected if the B-replier, after having  
 15 established connection with the device according to the invention, e.g. by means of a special prefix or SMS (and initially authenticated by the caller-ID), activates the device to receive an improvised temporary single use code, which within a certain period of time must be repeated from the keypad connected to the device according to the invention in order to be an accepted command, and which thereafter is no longer valid. The visitor is  
 20 in this case reconnected into the call and advised to dial this code on the keypad of the device, which acts on the command, the proximity of the visitor also being made certain. In an analogous manner also expected visitors (without mobile phone) can in advance be given a code which is programmed in to be valid one time (at e.g. a party, several) at a given time interval, as well as an essentially immediate one-time-code can be given if e.g.  
 25 someone impromptu calls from a nearby pay phone. Fixed codes may thus (with individual time zone validity) be reserved only for certain authorized people, service staff, etc., whereby the risk for codes becoming known is reduced. All transactions (also entrance calls) will be "numerically linked" and may thus be saved to track improper use, if required. Sometimes the mere storing/saving of the number of a calling party, e.g. a not preauthoriz-  
 30 ed mobile phone, could be sufficient criterion for allowing at least partial access, e.g. customer's entry to shop open for business but locked to the (troublesome) street, permit to buy petrol at cash petrol pumps without first going in to the counter and pay in advance, and can be further specified by customer's instructed manually repeated input of the number on actual door's, pump's etc. possible keypad.

Should a B-replier use call forwarding for his telephone and still wish to maintain opening capability, the device according to the invention may after a call from the preprogrammed (authorized) telephone and a suitable prefix, master code, SMS or similar be updated with relevant number (that which is forwarded to and from which an opening would be  
 5 effectuated), active time period, etc.. Also other real time programming of the device according to the invention can be made by a telephone call (and also via modem etc.) in a similar way.

Another added feature according to the present invention for more advanced, speedy and  
 10 enhanced use than what is possible by just by pushbutton operation etc. on a mobile phone or apparatus keypad can be a "cradle" (or other short range communication unit) into which the visitor can place his mobile telephone on request from the B-replier and after having completed initial communication with same. This "cradle", similar to the old 1970's telephone modems has a microphone and loudspeaker and can thus in such a situation  
 15 transmit/receive rather advanced data communication between a device according to the invention and B-replier via the visiting mobile, (as complement or alternative) provide for the earlier mentioned initial and also here with reciprocity possible "ID-check", and thus facilitate rather complicated transactions as services to the visitor, for example, issuing tickets, cash machines, payment machines for parking, automatic machines for supply of  
 20 goods etc., and may be suitable for more elaborate applications, probably not for pure man-to-man-communication, such as entrance telephone installations.

Since an own permanent connection to a telephone network for a device according to the invention has not been mentioned in the above situation, it should be recognized that same  
 25 actually does not need to exist. It can have it or not have it. It can in the latter case instead (via the cradle and visitor mobile) occasionally "take over" the visitor's subscription and thus virtually be telephone network connected per each transaction. If it has its own permanent telephone network connection and given telephone number, which however is more expensive both by its then construction and connection, it can then be called by the  
 30 B-replier as above earlier described, the B-replier's authority being cleared by the caller-ID, and the cradle link merely used for complementing same and/or enhancing etc. a transaction (e.g. mobile connections are speedier than landline). If it doesn't have these own permanent features, all authority ID-data can be fully included in the transaction signal/data cradle link connection and communication. A user with a mobile telephone calls  
 35 a number stated by the installation which includes the "cradle" and receives contact with

a machine/person requesting information of the user's desired purchase, credit card number and similar. When communicating with a machine, choice and input of information can be made via the keypad of the mobile telephone. When required information relating to the transaction has been inputted/accepted, the user receives a request to place the mobile telephone in the "cradle" (not disconnected) and to, for example, depress a button adjacent to the "cradle". Hereby the local unit installation is "lended" the visitor's subscription and call, and becomes thus telephone network connected/linked (per 020-number the "loan" can be repaid, and can the couple thus with fair business ethics also be used for apparatus update/programming etc. in real time, and if speech audio part, also conversation can be by command upheld). Hereafter communication takes place between the local unit and called unit according to a predetermined signalling protocol, preferably by a signal modem. In order to ensure required security, the communication can be coded, including a coded check sum, or authenticated in other known way. When communication has been completed (and user possibly made a payment transaction), the user may, for example, receive a message from the local unit to remove the mobile telephone from the "cradle" and to terminate the call. Hereafter can the local unit print a ticket or other type of verification or service for intended purpose. This might be suitable in cases when, for example, an own permanent connection to a telephone network is difficult/vulnerable to abuse or the application does not motivate the extra cost and administration involved for an own permanent connection to a telephone network.

As example of a related embodiment can, for example, be mentioned the possibility to use units not connected to a telephone network in connection with holiday cabins, hotels and similar, whereby a user can establish connection to an administrative centre via the mobile telephone, and request to rent a cabin, room or similar. After acceptance of the transaction, which may include transfer of e.g. credit card information from a user, the mobile telephone is placed in the aforementioned "cradle", whereafter required information for permitting access is transferred. The local unit may now as an alternative for example perform lock opening, but same may also be equipped to manufacture a "key" to the rented object, which for example can be a printout of a bar code, a card with an information carrying magnetic strip, or a punched key card. Such a key may obviously also include information relating to the length of the rented period, and when said period expires be blocked against further use. Such an embodiment means that the local unit does not require any own permanent fixed or mobile telephone network connection, since communication between administrative central unit and local unit is carried out utilizing the



mobile telephone of a user. Similar applications may involve issuance of tickets and other documents, delivery of goods from vending machines, etc., based on information transferred between an administrative centre and the machine having the above mentioned "cradle", and especially perhaps in countryside installations.

5

Should the invention be used for a building having its own local exchange, it may be arranged in such a fashion that all extensions can open free of charge during office hours and (typically in night mode and with relevant preprogrammed home numbers) also from home, which would however normally involve a call charge for opening.

10

With regard to buildings having only single or a few tenants (and just one telephone line), the costs involved for a separate telephone network subscription would be a disadvantage. However, with an ISDN subscription, one of the channels can be used without any additional cost. Furthermore, mobile and fixed telephone network subscriptions (refill or  
15 invoiced) are today offered with two telephone numbers, whereby one can be used to check the number ID from the other. WLAN-telephones are also more frequently used, and involve often a PABX function, which makes it possible to connect a further individual identity (number). Should one of these extensions be used by the device according to the invention, access can be controlled by the other. More contrived, a device according to the  
20 invention can be put and configured to constantly monitor a house's sole (fixed) telephone line, and per a DTMF-receiver detect all the numbers dialled by the house telephone(s). When a such number (after line tone) is the house's own (or other programmed number, e.g. ##5, where ## can cut CO line, so just house can open), it can (by the dialled number-ID) start listen for the busy tone that now will commence (this to  
25 exclude numbers dialled by external parties in call), and at the right "mix" (line tone+number+busy tone) allow access. More hypothetically, perhaps the "off hook" caller-ID variant (which give the ID of a calling party even when a call is on, it is also called "call-waiting" ID, and is presently implemented in a few countries) could be used, meaning that caller-ID could be given also when calling one self, so to say. Much depends here on how  
30 the actual network operator now and henceforth shapes and provides it's caller-ID service (at present there is no common "global" standard), as also how future telecommunication's systems may be configured; and it could thus be here appropriate to generally state that the thought/scope of the present invention is felt to be valid evenso, as also should certain elements/features of this invention be placed centrally (in CO/base station/server/etc.) by  
35 the operator.

It is also possible to avoid call charges for a request to open the entrance lock. When the B-replier has talked to a visitor and wishes to allow access, a call to the device according to the invention would indicate the number ID (Caller-ID) to the call receiving device, which could be set to only answer incoming calls after a certain number of ring signals, e.g. five.

- 5 Should the B-replier terminate the call earlier, e.g. after two ring signals, such an action could be interpreted as a direct command to unlock the entrance door. Since the called device receives the number of the calling party without answering the call, the ID can be checked and approved as an authorized B-replier, and the short call period (2 ring signals) in combination with received ID would be a command to open the entrance door lock. No
- 10 call charge would be involved. (A similar protocol and say one ring signal, would also make it possible for an inprogrammed cellphone of e.g. a family member to open e.g. a motorized garage door of a bungalow, by calling that house's landline telephone to which the device is parallely connected, and still, by letting more signals go, allow for regular telephone conversation after reply, and without opening, in an akin way, for the earlier
- 15 discussed situation of a house having only one incoming (land)line, a mobile of an inside family member can provide access for visiting guests. The role of a possibly influencing B-replier will in these two situations be that of a person inside the house, in the first: if and when replying on the landline phone; in the second: placing the mobile call.)
- 20 On the other hand, should the B-replier allow (in this example) five ring signals, the called device will answer the call, and the ID-validated B-replier would now be able to perform service requests (i.a. opening) by inputting predetermined code sequences per DTMF. This means that normally a call charge is involved, whereas simple lock opening commands (as described above) would be free of charge. A B-replier can (by program-
- 25 ming) individually define whether its number immediately should lead to direct access or service requests/signalling, and shifts therebetween can also be time-zoned. This could be advantageous for e.g. tenants and nighttime. A more basic embodiment, always jsut giving direct access without taking the call, is also readily feasible. Also, by counting the ring signals without taking the call, at least two different actions can be taken free of
- 30 charge, e.g. open for less than 3 and activate a code lock sequence for more than 5 signals. If the called device (in e.g. apartment buildings) have two incoming lines (numbers), one number called could provide direct access free of cost, while the other number could be put to take its call (at a cost) and so (after ID-check) allow more advanced control signalling, programming etc.. Two (or more) incoming lines obviously
- 35 also generally would increase the over-all capacity of larger installations. One can also

here mention that if the "off hook" caller-ID service is available with installations where one central called device unit (having only one incoming line) is to handle several access points, direct access could be given to one point (by the "off hook"-ID), even when the central unit is busy on the telephone line with a more elaborate and time consuming access signalling for another. If only direct access is on, though, handling times are so short that conflicts are unlikely, and so "off hook" caller-ID would not be very vital; and concurring code/card/etc. access can of course also be handled.

With regard to entrance telephone systems, and other existing systems for control and access, such as for instance intercoms (group A), code/card/biometrical readers, telephone entry systems (group B), mere pushbutton or remote control operated electrical door strikes (all hereinafter commonly referred to as "access control systems"), the method according to the present invention can in most cases be implemented with major parts of previous installation unchanged. It is also possible to modify such earlier installations in such a way that previous system is maintained in parallel with the method according to the invention. As a result, for example, certain tenants may prefer to use the cost effective method according to the present invention, whereas other tenants may prefer to use existing system, e.g. with entrance calls being switched through via the public telephone network to their ordinary telephone.

20

Whereas thus preexisting access control systems can be upgraded to include the present invention, as well as someplace basic entry/access control can be newly established by applying an according to the invention relevantly programmed and organized common caller-ID device, a separate advantageous embodiment of the present invention, primarily useful for apartment buildings, gated communities etc., is realized, which is already when manufactured built to combine "classical" telephone entry with the present invention's essentially as hereinabove disclosed caller-ID concept, into one integrated system. It will need just one telephone line and number for performing "both ways", and since it for the classical dial-up modality needs both microphone and speaker and also a keypad, same can be used also for maintaining conversation in a "dial-down" caller-ID version communication (by preprogram or letting e.g. five signals go and then by DTMF command activate the speech), and for code lock use. Each B-replier's choice of modality and available features can be individually assigned per programming, and also time zoning hereof is possible. E.g. small offices, surgeries, can have both ways at the same time, accepting the (separately billed) charges for dialling up by the system by customers without

35

mobile phones, as well as giving customers with mobiles the convenience of not having to stand outside before the entrance the whole time of dial-up, conversation and unlock, but being able to do much of it on approach. Normally, then, dial-up by the system to B-repliers having chosen caller-ID modality, is not allowed (and so they may be spared from running call charges of others). Since however the system would have a telephone number, that same easily recognisable number will appear for a called B-replier having a caller-ID (even busy in a call, if off hook ID). This can be separately used (most likely quite infrequent, and programmable, and for just B-repliers having chosen their telephone numbers to be thus accessible; but mentioned here just as a technical possibility within the inventive thought) to giving visitors a possibility to call such B-repliers by the system, free of cost. When such a B-replier number is thus called, it can ring very shortly and then break, i.e. before reply and thus cost. But the B-replier is now by the caller-ID (which furthermore can be of the standard type having a so called VIP-number facility = audio/opto alert for some programmed number, and/or facility for automatic dial of last incoming number) intimated of the call, and can in its turn call up the system, either direct give access, or entering into speech/signalling phase.

Alarm control systems (to-day almost all telephone linked), especially surveillance systems type fire, medical/elderly care etc., have so far had problems with legitimate access (entry) for personnel at call to actual alarming site, if locked. At e.g. fire brigade call, must often a special unit bringing a great number of coded keys, whereof one is supposed to open the door, arrive, so that the entranced door should not have to be forced by fire axes etc.. This is a both administrative and cost problem and with uncertain synchronization. By integrating, or complementing with, a device according to the present invention into an alarm control system, a solution hereto would with good congruence and security be given, by synergic call-up from an area-wise inprogrammed operative center, and thus can opening be effectuated at received authorized ID. This also has the advantage over distributed (e.g. per local personnel's probably diverse numbers) authentication, that only a few numbers which furthermore always can be expected to be at hand, here need to be inprogrammed for the whole area, town etc.. Also caller-ID authenticated steering, programming, operation control etc. as earlier herein described can advantageously be here implemented, and can combined with i.a. entry control as hereinabove described, lead to fully integrated systems for building management, also including such things as caller-ID administrated booking of laundromats, swimmingpools, gyms etc. Above described integration/complementing can be done at manufacture or as a retro-fit.

Also more service orientated entry, like postal etc. delivery, can in an analogous way be provided, better safeguarded than today's postal locks/codes etc. against unwanted circulation of "keys", either distributed, by the deliverer's own relevantly inprogrammed standard or specially adapted (perhaps just having a telephone number, line seizing and  
 5 dialling) telecom instrument; or centrally, by en route addressing a central which thereupon by its (for all actual entrances jointly inprogrammed and, as in most cases hereinabove, preferred landline) telephone, can execute an authorized opening call-up to directed entry installation, preferably landline connected.

10 The fact that SMS and EMS/MMS arrives on the same signal protocol as Caller-ID (FSK) and starting with same, nowadays also on landline phones and in real time (without lag), means that they readily can be received and decoded by the present invention for giving a calling party (authorized by the initializing caller-ID when calling from the "home" telephone) possibility for the cost of one such message to comprehensively programming  
 15 and commanding a device according to the present invention, and so they are meant included in the inventive thought herewith. When not calling from the home phone, all authentication ID can be safely included in the message and the invention, knowing it to be an SMS, can ignore the preceeding caller-ID. It can also be used, however, to create a transaction record; check it against a list of preauthorized numbers; call back upon  
 20 completion of desired action as a receipt and which could consist of either just the invention's own telephone number, readable as a caller-ID for the first calling party (even without same taking the call so no cost is incurred), or be sent as an SMS back to same. Protocols like this can also apply for all other embodiments above.

25 The present invention is thus not restricted only to applications relating to entrance telephone applications and similar, since the principles disclosed for access control to a building also can be used for various types of safe transactions with use of a mobile telephone, and with a device according to the invention communicating with a fixed telephone network, a mobile telephone network, as well as without any own network  
 30 connection (cf. the example of a key delivering machine described earlier).

## CLAIMS

1. Method for communication/control of access, including the steps:  
5 that a person wishing to use the method for obtaining access as an initial step via telephone or other communication means at hand establishes contact with a machine or person (B-replier);  
10 that as a subsequently following step contacted machine/person (B-replier) on basis of obtained verbal or signalled information evaluates whether or not requested access should be allowed; and  
that as a final step, on accepted received information from the calling person, contacted  
15 machine or person (B-replier) initiates performance of required action by connection to and signalling via fixed or mobile telephone network its authorization and request for services to an influenceable unit providing the access service, which, on acceptance of received signals/data, performs required action.
- 20 2. Method according to claim 1, **in which** received signals/data comprises regular number representation/(caller-ID) information.
3. Method according to claim 1, **in which** the final signalling from the B-replier also may be a fixed execution of said initial/prior steps, and that the interaction from the visitor  
25 may vary.
4. Method according to any one of claims 1 - 3, when the initial step of the B-replier is performed by a person authorized to enter a building/area to which a visitor wishes to gain access, and **characterized in**  
30 that during the final step, the B-replier calls/addresses a telephone network connected influenceable unit which performs control of the B-repliers authority by checking whether or not the addressing number is an approved telephone number or similar;  
35 that acceptance as a correct addressing number allows or effectuates performance of a

predetermined action;

that the B-replier optionally further can perform input of a code sequence by means of its keypad or similar; and

5

that inputted code sequence is checked by the called unit, and on acceptance as a correct sequence, results in performance of a predetermined action.

5. Method according to any one of claims 1 - 4, **characterized in** that the B-replier  
10 performs input/activation of a freely chosen code sequence which during a predetermined period of time can be used as an activating code by an outside keypad for gaining access.

6. Method according to any one of claims 1 - 3, **characterized in** that the final step  
15 involves that the visitor places utilized mobile telephone against a "cradle" or other means while maintaining a switched through connection to the B-replier, thereby transferring signal communication from the user to the influenceable unit and establishing a two-way signalling connection between B-replier and influenceable unit;

that information between influenceable unit and B-replier is exchanged via established  
20 connection; and

that after completed and approved step with transfer of information the influenceable unit performs printout/dispension of ticket/document/service/goods requested by the visitor during initial communication with the B-replier.

25

7. Method according to any one of claims 1 - 6 related to an entrance telephone installation, **characterized in** that connected tenants or similar are divided into two or more groups having from each other different status, e.g. entrance calls charged to the visitor's mobile telephone, call charge(s) accepted by tenant (020-status) etc.

30

8. Device for communication/control of access utilizing the method according to claims 1 - 7, **characterized in** that the influenceable unit is permanently connected to a fixed or wireless telephone network, primarily arranged to accept only incoming calls.

35 9. Device for communication/control of access utilizing the method according to

claims 1, 3 and 6, **characterized in** that the influenceable unit is not permanently connected to a fixed or wireless telephone network, but includes a device by means of which a visitor can place his mobile telephone while in a connected condition to the B-replier in order to establish a telecom connection and a two-way signalling connection  
 5 between influenceable unit and the B-replier, whereby required exchange of information between B-replier and influenceable unit relating to approved action is transferred via thus established connection.

10. Device according to claim 8, **characterized in** that the telecom connection for  
 10 the influenceable unit is arranged to facilitate outgoing calls from alarm sensors, which preferably are given priority over incoming calls.

11. Device according to any one of claims 8 - 10, **characterized in** that a receiver for reception of Caller-ID is integrated.  
 15

12. Device according to any one of claims 8 - 11, **characterized in** that a code lock device is integrated.

13. Device according to any one of claims 8 - 12, **characterized in** that a keypad  
 20 is integrated.

14. Device according to any of claims 8 - 13, **characterized in** that a speech/audio part is integrated.

25 15. Upgrading/complementing a system of a type selected from the group consisting of an access control system, an alarm control system and a combined access control and alarm control system with a device according to any of claims 8 - 14.

16. A system of a type selected from the group consisting of an entrance telephone  
 30 system, an alarm system and a combined entrance telephone system and alarm control system wherein a device according to any of claims 8 - 14 is integrated.

17. Method according to any one of claims 1 - 4, **in which** reading and temporary storing/saving of the number of a visiting telephone gives access to commencing part of  
 35 a follow-up transaction.



18. Device which in normal case utilizes the method according any one of claims 1 - 7, **in which** independently of exact or internally related execution of said steps, the influenceable unit via an integrated caller-ID (number presenting device) directly after receipt and checking of an authorized number performs corresponding final function.

5

19. Method according to anyone of preceeding claims, in which communication to and/or from a user is completely or partially communicated as SMS and/or EMS/MMS.

ABSTRACT

A method and a device for communication/control of access, the term access including access to services and or goods. According to the invention should a person wishing to  
5 use the method for obtaining access establish contact via telephone with machine or called person (B-replier); as a following step should said person, verbally or by signalling via existing keypad, request access; and as a subsequently following step evaluates contacted machine/person (B-replier) whether or not the request for access should be accepted; and as a final step, on accepted received information from the calling person, initiates called  
10 machine or person (B-replier) performance of relevant action by signalling to the required unit. When the B-replier is a person within a building, the final step is performed by a call from the B-replier to a telephone network connected device, which checks the authority of the call by means of the callers number ID against a preprogrammed list of accepted telephone numbers, and on acceptance, the B-replier can further input a code sequence  
15 by means of the keypad, which is checked by the called unit, which performs a for the specific sequence related action. According to one embodiment, the user's own mobile telephone is used for the final step, placed connected to the B-replier in a "cradle" facilitating two-way data communication between the acting unit and the B-replier.